

## Product: <u>FWSWBF02LD</u> 🛛

# WALL-BOX, CONSOLIDATION WORKSTATION SPLICE OS2

### **Product Description**

FX WALL-BOX FIELD-TERM, 2-PORTS, OS2, LC DUPLEX, BLUE ADAPTERS

#### **Technical Specifications**

IMAGE COMING SOON

#### **Product Overview**

Environmental Space: Indoo		loor			
Suitable Applications:	FiberExpres	FiberExpress Ultra Solutions, Backbone, Telecommunications Room, Main Distribution Room, Workstation Are			
Construction					
Height: 0.394 in					
Width: 3.385 in					
Depth:	3.385 in				
Physical Specifica	tions				
Max Capacity:	2 LC Duples	2 LC Duplex Adapter			
Mechanical Chara	cteristics				
Front Connection:	Static	Static			
Comperature Range Operating Temperature R Storage Temperature Ra	Range: -10°C to 60°				
otorago romporataro ra					
Product Material					
Product Material Materials					
	Material	Color Type			
Materials Description	Material Plastic - UL94V-0	Color Type Black			
Materials Description Floor Box Base					
Materials Description Floor Box Base Floor Box Bottom Cover	Plastic - UL94V-0	Black			
<b>N</b> aterials	Plastic - UL94V-0 Metal	Black Black			
Materials Description Floor Box Base Floor Box Bottom Cover Floor Box Top Cover	Plastic - UL94V-0 Metal Metal	Black Black Company Compan Company Company Co			

#### elated Part Numbers

Related Parts:	FX UHD & FXU PATCH PANELS, FX MPO TRUNKS, FX PATCH CORDS
Product Notes	
Packaging:	Individually packaged in a Korrvu box
History	
Update and Revision:	Revision Number: 0.141 Revision Date: 02-12-2025

#### © 2025 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.