



**Product:** [GIOTAG1](#)

Indoor tight buffered pigtail LSZH jacket Colored fiber for pigtail Simplex SM OS2 G.652.D & G.657.A1.

**Product Description**

Indoor tight buffered pigtail with Low Smoke Zero Halogen outer jacket. Colored fiber for pigtail Simplex SM OS2 G.652.D & G.657.A1.

**Technical Specifications**

**Product Overview**

Construction Type:	Interconnect
Environmental Space:	Indoor (Not Riser or Plenum)
Suitable Applications:	Flexible terminating leads such as pigtails, patchcords and test leads. Support all computer network applications such as FDDI, Gigabit Ethernet and ATM. Short distance applications for indoor use.

**Construction**

**Fiber Cable Construction**

Fiber Type	Fiber Grade acc. ITU-T	Fiber Count
OS2	G.652D & G.657A1	1

**Buffer Specification**

Fiber Type	Buffer Construction	Buffer Material	Buffer Diameter
OS2	Tight	LSZH - Low Smoke Zero Halogen (Flame Retardant)	0.9 mm

Bulk Cable Weight:	0.67 kg/km
--------------------	------------

**Jacket Specifications**

Number of Jackets:	Single Jacket
Type of Armor:	Non-Armored

**Outer Jacket Specifications**

**Outer Jacket**

Material	Nominal Diameter	Ripcord
LSZH - Low Smoke Zero Halogen (Flame Retardant)	0.9 mm	No

Table Notes:	Standard color: Orange. Available colors: Orange, Yellow, Turquoise, Erika Violet, Red, Blue, Green, Brown, Violet, Pink, Grey, White, Black, Lime Green
--------------	--

**Optical Characteristics**

Max. Attenuation at 1310 nm:	0.40 dB/km
Max. Attenuation at 1550 nm:	0.30 dB/km
Max. Attenuation at 1625 nm:	0.30 dB/km

**Mechanical Characteristics**

**Mechanical Tests**

Description	Tested Standard	Requirement/Value
Cable Max. Tensile Strength Installation (Short Term)	IEC 60794-1-21-E1	3 N (1 lbf)
Cable Max. Tensile Strength Operation (Long Term)	IEC 60794-1-21-E1	1 N (0 lbf)
Cable Max. Crush Resistance Installation (Short Term)	IEC 60794-1-21-E3	0.5 kN/m

## Temperature Range

Operating Temperature Range:	-40 °C to +70 °C
Installation Temperature Range:	-15 °C to +50 °C
Storage Temperature Range:	-40 °C to +70 °C

## Standards

UL Rating/Flame Test:	Non-UL Rated
IEC 60754-1 - Halogen Amount:	Zero
IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity:	10 µS/mm
IEC 60754-2 - Halogen Acid Gas Amount - Min. pH:	4.3
REACH:	Compliant
ISO/IEC Compliance:	IEC 60794, ISO/IEC 11801-1
EU Directive 2011/65/EU (RoHS 2):	Compliant
UV/ Sunlight Protection:	Yes

## Related Part Numbers

### Variants

Item #	Color	Put-Up Type	Length	EAN
GIOTAG1.002100	Black	Reel	2,100 m	8719605074980
GIOTAG1.102100	Blue	Reel	2,100 m	8719605075086
GIOTAG1.042100	Brown	Reel	2,100 m	8719605075024
GIOTAG1.082100	Gray	Reel	2,100 m	8719605075062
GIOTAG1.052100	Green	Reel	2,100 m	8719605075031
GIOTAG1.062100	Orange	Reel	2,100 m	8719605075048
GIOTAG1.092100	Pink	Reel	2,100 m	8719605075079
GIOTAG1.072100	Red	Reel	2,100 m	8719605075055
GIOTAG1.112100	Turquoise	Reel	2,100 m	8719605075093
GIOTAG1.032100	Violet	Reel	2,100 m	8719605075017
GIOTAG1.012100	White	Reel	2,100 m	8719605074997
GIOTAG1.022100	Yellow	Reel	2,100 m	8719605075000

## History

Update and Revision:	Revision Number: 0.156 Revision Date: 09-17-2024
----------------------	--

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.