

Product: <u>H18X0.75</u> ☑



MachFlex[™] 610YY Control & Power Cable, 18 C 0.75mm² Str BC, PVC Ins, PVC Jkt

Product Description

MachFlex™ 610YY Control & Power Cable, 18 Conductor 0.75mm² Stranded Bare Copper, PVC Insulation, PVC Jacket

Technical Specifications

Product Overview

| Suitable Applications: | uitable Applications: Designed for applications which are installed in occasional flexing and fixed locations. Cable applications include precision control sensors, multi axis control machines, temperatur controllers, control panels, machine cutting tools, auxiliary equipment, motor speed control, production machinery and many more. | | | |
|------------------------|--|--|--|--|
| Construction Details | | | | |
| Conductor | | | | |

| Element | No. of Elements | Size | Stranding | Stranding Class | Material |
|--------------|-----------------|----------------------|-----------|-----------------|------------------|
| Conductor(s) | 18 | 0.75 mm ² | Stranded | Class 5 | BC - Bare Copper |

Insulation

| Element | Material | Color Code |
|--------------|-----------------------------|---|
| Conductor(s) | PVC - Polyvinyl Chloride | Black #1, Black #2, Black #3, Black #4, Black #5, Black #6, Black #7, Black #8, Black #9, Black #10, Black #11, Black #12, Black #13, Black #14, Black #15, Black #16, Black #17, Black #18 |

Outer Jacket

| Material PVC - Polyvinyl Chloride | |
|--------------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 15.3 mm (0.602 in) |

Electrical Characteristics

| Voltage Rating |
|---|
| 600/1000 V (Max. Operating Voltage), 4000 V (Testing Voltage) |

Mechanical Characteristics

| Temperature | | | | |
|---------------------------------------|---|------------------------------------|--|--|
| Operating | | Installation | | |
| -5°C to +70°C(Occasiona | al movement) | -40°C to +80°C(Fixed installation) | | |
| Bend Radius | | | | |
| Installation Min. Flexing Min. | | | | |
| 61.2 mm (2.41 in) 229.5 mm (9.035 in) | | | | |
| Bulk Cable Weight: | Bulk Cable Weight: 335 kg/km (225 lbs/1000ft) | | | |
| Standards and Co | mpliance | | | |
| Environmental Suitability: | Sunlight Res | istance, UV Resistance, Oil Resis | | |
| Flammability / Reaction to Fire: | IEC 60332- | 1-2, DIN VDE 048233212, DIN E | | |
| ISO/IEC Compliance: | IEC 60228 | | | |

| CENELEC Compliance: | EN 50290-2-22 | | | |
|---|---|--|--|--|
| European Directive EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2) | | | | |
| Other Standard Compliance(s): | IEC 60227-5, EN 50525-2-51, DIN VDE 0207-363-4-1, VDE 0295, BS 6360 | | | |

History

Update and Revision: Revision Number: 0.59 Revision Date: 07-15-2024

Part Numbers

Variants Coloi Length H18X0.75 010100M Black 100 m H18X0.75 010200M Black 200 m H18X0.75 010300M Black 300 m H18X0.75 006100M 100 m Blue H18X0.75 006200M Blue 200 m H18X0.75 006300M Blue 300 m H18X0.75 G8U100M Gray, RAL 7001 100 m H18X0.75 G8U200M Gray, RAL 7001 200 m H18X0.75 G8U300M Gray, RAL 7001 300 m

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.