



Product: [IEA004](#)

High Flex Cat 6A 24AWG

Product Description

DATATUFF INDUSTRIAL ETHERNET SHIELDED CAT6A, 4 PAIR 24AWG (STRANDED 7X32) TINNED COPPER, HDPE INSULATION, X-SPLINE, TPE OUTER JACKET, UL CMR RATED, CMX OUTDOOR RATED, OIL RES II, SUN RES, AWM 600V

Technical Specifications

Product Overview

Suitable Applications:	High Flex, Automation, Robotics, exposure to oil and gasoline, harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc.
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
24	7x32	TC - Tinned Copper	4

Insulation

Material	
PE - Polyethylene	
Bonded-Pair:	No

Color Chart

Color
White/Blue & Blue
White/Orange & Orange
White/Green & Green
White/Brown & Brown

Outer Shield

Type	Material	Coverage [%]
Tape	Bi-Laminate (Alum+Poly)	100%
Braid		75%

Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness
TPE - Thermoplastic Elastomer	.322 in.	.033 in. mm

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. DCR Unbalance
14 Ohms/100m @ 20C	0.04 %

Capacitance

Nom.Mutual Capacitance
17 pF/ft

Delay

Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
540 ns/100m	45 ns/100m	67%

High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2.5 dB/100m	74.3 dB dB	72.3 dB dB	67.8 dB	64.8 dB	20.0 dB	100 +/- 15 Ohms	100 +/- 10 Ohms	40.0 dB	35.0 dB
4 MHz	4.6 dB/100m	65.3 dB dB	63.3 dB dB	55.8 dB	52.8 dB	23.0 dB	100 +/- 15 Ohms	100 +/- 15 Ohms	40.0 dB	23.0 dB
8 MHz	6.4 dB/100m	60.8 dB dB	58.8 dB dB	49.7 dB	46.7 dB	24.5 dB	100 +/- 15 Ohms	100 +/- 15 Ohms	40.0 dB	16.9 dB
10 MHz	7.1 dB/100m	59.3 dB dB	57.3 dB dB	47.8 dB	44.8 dB	25.0 dB	100 +/- 15 Ohms	100 +/- 15 Ohms	40.0 dB	15.0 dB
16 MHz	9.0 dB/100m	56.2 dB dB	54.2 dB dB	43.7 dB	40.7 dB	25.0 dB	100 +/- 15 Ohms	100 +/- 15 Ohms	38.0 dB	10.9 dB
20 MHz	10.1 dB/100m	54.8 dB	52.8 dB	41.8 dB	38.8 dB	25.0 dB	100 +/- 15 Ohms	100 +/- 15 Ohms	37.0 dB	9.0 dB
25 MHz	11.3 dB/100m	53.3 dB	51.3 dB	39.8 dB	36.8 dB	24.2 dB	100 +/- 15 Ohms	100 +/- 15 Ohms	36.0 dB	7.0 dB
31.25 MHz	12.6 dB/100m	51.9 dB	49.9 dB	7.9 dB	34.9 dB	23.3 dB	100 +/- 15 Ohm	100 +/- 10 Ohm	35.1 dB	5.5 dB
62.5 MHz	18.0 dB/100m	47.4 dB	45.4 dB	31.9 dB	28.9 dB	20.7 dB	100 +/- 15 Ohm	100 +/- 10 Ohm	32 dB	
100 MHz	23.0 dB/100m	44.3 dB	42.3 dB	27.8 dB	24.8 dB	19.0 dB	100 +/- 15 Ohm	100 +/- 10 Ohm	30.0 dB	
200 MHz	33.1 dB/100	39.8 dB	37.8 dB	21.8 dB	18.8 dB	19.0 dB	100 +/- 22 Ohms	100 +/- 10 Ohms	27.0 dB	
250 MHz	37.3 dB/100m	38.3 dB	36.3 dB	19.8 dB	16.8 dB	15.6 dB	100 +/- 32 Ohms	100 +/- 10 Ohms	26.0 dB	
300 MHz	41.1 dB/100m	37.1 dB	35.1 dB	18.3 dB	15.3 dB	14.9 dB	100 +/- 32 Ohms	100 +/- 10 Ohms	25.2 dB	
400 MHz	48.1 dB/100m	35.3 dB	33.3 dB	15.8 dB	12.8 dB	13.8 dB	100 +/- 32 Ohm	100 +/- 10 Ohm	24.0 dB	
500 MHz	54.3 dB/100m	33.8 dB	31.8 dB	13.8 dB	10.8 dB	13.0 dB	100 +/- 32 Ohm	100 +/- 10 Ohm	23.0 dB	

Voltage

UL Description	UL Voltage Rating
UL 2463	600 V

Temperature Range

Installation Temp Range:	-20°C To +80°C
UL Temp Rating:	80°C
Storage Temp Range:	-40°C To +80°C
Operating Temp Range:	-40°C To +80°C

Mechanical Characteristics

Oil Resistance:	Oil Res II
Bulk Cable Weight:	48 lbs/1000 ft
Max. Pull Tension:	32 lbs
Min. Bend Radius During Installation:	2.58"

Standards

NEC/(UL) Compliance:	UL 444
UL AWM Style Compliance:	2463
Data Category:	Category 6A

Applicable Environmental and Other Programs

EU Directive 2011/65/EU (RoHS 2):	Yes
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	No
Suitability - Oil Resistance:	Yes
Suitability - Outdoor:	Yes

Suitability - Sunlight Resistance:	Yes
------------------------------------	-----

Flammability, LSOH, Toxicity Testing

UL Flammability:	UL 1666 - Riser
------------------	-----------------

History

Update and Revision:	Revision Number: 0.19 Revision Date: 09-08-2021
----------------------	---

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.