




Product: [MRG1740](#)



MRG1740 - 50 Ohm Wireless Transmission Coax, RG174 Type, 26 AWG Solid BCCS, 85% TC Braid, PVC Jkt

### Product Description

50 Ohm Wireless Transmission Coax, RG174 Type, 26 AWG Solid Bare Copper Covered Steel Conductor, PE Insulation, 85% Tinned Copper Braid Shield, PVC Jacket

### Technical Specifications

#### Product Overview

Suitable Applications:	Point-to-point and point-to-multipoint wireless antenna communication; Wireless microphones, Two-Way Radios, Amateur (Ham) Radio, Low Power FM, GPS, RFID (Radio Frequency Identification)
------------------------	--

#### Construction Details

RG Type:	174
----------	-----

#### Conductor

No. of Elements	Size	Stranding	Nom. Diameter	Material
1	26 AWG	Stranded	0.48 mm	BCCS - Bare Copper Covered Steel

#### Insulation

Element	Material	Nom. Insulation Diameter
Insulated Conductor	PE - Polyethylene	1.5 mm (0.059 in)

#### Outer Shield

Outer Shield Type	Material	Coverage
Braid	Tinned Copper (TC)	85%

#### Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	2.8 mm

Table Notes:	According to EN 50290-2-20
--------------	----------------------------

#### Electrical Characteristics

#### Attenuation

Frequency	Nom. Attenuation
10 MHz	11 dB/100m
200 MHz	42 dB/100m
1000 MHz	110 dB/100m

Table Notes:	Max. attenuation 10% higher
--------------	-----------------------------

#### Electricals

Max. Conductor DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
317 Ohm/km (96.6 Ohm/1000ft)	100 pF/m (30 pF/ft)	50 Ohm	66%

#### Voltage

Voltage Rating
1400 V DC / 1000 V RMS

## Mechanical Characteristics

### Temperature

Operating	Installation	Storage
-40°C To +70°C	-5°C To +50°C	-40°C To +70°C

Max. Pull Tension: 90 N (20 lbf)

### Standards and Compliance

Environmental Suitability:	Indoor - Euroclass Eca
Flammability / Reaction to Fire:	IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca; CPR UKCA Class: Eca
Military Compliance:	MIL-C-17
European Directive Compliance:	EU CE Mark
UK Regulation Compliance:	UKCA Mark

### History

Update and Revision: Revision Number: 0.196 Revision Date: 12-22-2023

### Part Numbers

#### Variants

Item #	Color	Putup Type	Length	EAN
MRG1740.0050	Black	Reel	50 m	8719605102874
MRG1740.00500	Black	Reel	500 m	8719605102881

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.