




Product: [MRG223](#)



MRG223 - Mil-Spec Coax, 50 Ohm, RG-223, 19 AWG Solid SC, Double 95% SC Braid, PVC Jkt, Commercial

Product Description

Mil-Spec Coax, 50 Ohm, RG-223, 19 AWG Solid Silvered Copper Conductor, PE Insulation, Double 95% Silvered Copper Braid Shield, PVC Jacket, Commercial

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | Point-to-point and point-to-multipoint wireless antenna communication; Wireless microphones, Two-Way Radios, Amateur (Ham) Radio, Low Power FM, GPS, RFID (Radio Frequency Identification) |
|------------------------|--|

Construction Details

| | |
|----------|-----|
| RG Type: | 223 |
|----------|-----|

Conductor

| No. of Elements | Size | Stranding | Nom. Diameter | Material |
|-----------------|--------|-----------|---------------|----------------------|
| 1 | 20 AWG | Solid | 0.90 mm | SC - Silvered Copper |

Insulation

| Element | Material | Nom. Insulation Diameter |
|---------------------|-------------------|--------------------------|
| Insulated Conductor | PE - Polyethylene | 2.95 mm (0.116 in) |

Outer Shield

| Outer Shield Type | Material | Coverage |
|-------------------|----------------------|----------|
| Braid | Silvered Copper (SC) | 95% |
| Braid | Silvered Copper (SC) | 90% |

Outer Jacket

| Material | Nom. Diameter |
|--------------------------|---------------|
| PVC - Polyvinyl Chloride | 5.4 mm |

| | |
|--------------|----------------------------|
| Table Notes: | According to EN 50290-2-20 |
|--------------|----------------------------|

Electrical Characteristics

Return Loss (RL)

| Frequency | Min. Return Loss |
|-------------|------------------|
| 100-300 MHz | 35 dB |
| 300-900 MHz | 30 dB |

Attenuation

| Frequency | Nom. Attenuation |
|-----------|------------------|
| 50 MHz | 10.5 dB/100m |
| 230 MHz | 23.6 dB/100m |
| 470 MHz | 33.8 dB/100m |
| 860 MHz | 43.9 dB/100m |
| 1000 MHz | 54.2 dB/100m |

| | |
|--------------|-----------------------------|
| Table Notes: | Max. attenuation 10% higher |
|--------------|-----------------------------|

Electricals

| Nom. Conductor DCR | Nom. Outer Shield DCR | Nom. Capacitance Cond-to-Shield | Nom. Characteristic Impedance | Nom. Velocity of Prop. |
|--------------------|-----------------------------|---------------------------------|-------------------------------|------------------------|
| 28 Ohm/km | 4.5 Ohm/km (1.4 Ohm/1000ft) | 97 pF/m (30 pF/ft) | 50 Ohm | 66% |

Mechanical Characteristics

Temperature

| Operating | Installation | Storage |
|----------------|---------------|----------------|
| -40°C To +70°C | -5°C To +50°C | -40°C To +70°C |

Bend Radius

| Stationary Min. |
|-----------------|
| 50 mm (2.0 in) |

Standards and Compliance

| | |
|----------------------------------|---|
| Environmental Suitability: | Indoor |
| Flammability / Reaction to Fire: | IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca; CPR UKCA Class: Eca |
| Military Compliance: | M-17/84 |
| CENELEC Compliance: | EN 50117-1 |
| European Directive Compliance: | EU CE Mark |
| UK Regulation Compliance: | UKCA Mark |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.109 Revision Date: 05-31-2024 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | EAN |
|--------------|-------|------------|--------|---------------|
| MRG223.00100 | Black | Reel | 100 m | 8719605103161 |
| MRG223.00500 | Black | Reel | 500 m | 8719605103178 |

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.