

Product: PPFOUK-D ☑

PatchPro® - RFID Fiber Panel Upgrade Kit - 48-port - 96 Fiber - enhanced



## **Product Description**

PatchPro® - RFID Fiber Panel Upgrade Kit - 48-port - 96 Fiber - enhanced

## **Technical Specifications**

#### **Product Overview**

Environmental Space:	Indoor
Suitable Applications:	Horizontal and building cabling for Intelligent (RFID-based) patching in fiber systems, supporting current and future applications such as 10G Ethernet (10GBase-SR/LR), 40G Ethernet (40GBase-SR4/LR4), 100G Ethernet (100GBase-SR4/LR4), Fibre Channel, FDDI and ATM.

#### Construction

Weight:	449 mm
Overall Height:	15.4 mm
Overall Width:	449 mm

#### **Temperature Range**

Storage Temperature Range:	-20°C To +85°C				
----------------------------	----------------	--	--	--	--

### **Product Material**

### Materials

Description	Material	Color
LEDs	48 LEDs - Red	Black
Dimensions	(HxWxD) 15.4 x 449 x 4 mm	
Antenna Type	48 port 13.56MHz RFID antenna	
Power Consuption	400 mA max	

## **Standards**

EU Directive 2011/65/EU (RoHS 2):	Yes		

# **Related Part Numbers**

Related Parts:	It is suitable for use with the following LC Double Cassettes: PPLSMPOM, PPLAMPOM, PPL3MPOM, PPL4MPOM, PPL5MPOM, PPL5MPOM-ALT, PPLAMPOM-ALT, PPL4MPOM-ALT, and PPL5MPOM-ALT. In addition, it is compatible with the empty panel PP-1U-4DC and the PP range fiber patch cords.
----------------	---

## History

Update and Revision:	Revision Number: 0.7 Revision Date: 09-30-2025

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and

