



**Product:** [PPRO PP 1U 24P 10GX JACK UTP](#) 



PatchPro 24-port UTP Cat6A iPLM Ready Unshielded Panel, 1U, Packaging including 10GX RJ45 Unshielded Modular Jack

**Product Description**

PatchPro 24-port UTP Cat6A iPLM Ready Unshielded Panel, 1U, Packaging including 10GX RJ45 Unshielded Modular Jack

**Technical Specifications**

**Product Overview**

Suitable Applications:	Horizontal and building cabling for Intelligent (RFID based) Patching. Support current and future Category 6a and 6 applications, such as: 10GBase-T (10 Gigabit Ethernet), 1000Base-T (Gigabit Ethernet), 100 Base-T, 10 Base-T, FDDI, ATM
------------------------	---

**Physical Characteristics (Overall)**

Height:	45 mm
Width:	483 mm
Depth:	113 mm
Port Count:	24 Port
Front Connection:	Flush
Packaging:	Individually packaged in a box.

**Connectors**

**Materials**

Description	Material	Color
Panel	Zinc-coated Steel	Black
Body of connector	Plastic	Black

**Construction and Dimensions**

Max Capacity:	24 connectors
---------------	---------------

**Electrical Characteristics**

Dielectric Strength:	1,000 V RMS @ 60Hz for 1 minute
Current Rating:	1.500 A
Insulation Resistance:	500 MOhm Minimum
Max Contact Resistance:	20 mOhm
Termination Resistance:	2.5 mOhm

**Temperature Range**

Installation Temp Range:	-10°C To +60°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-10°C To +60°C

**Mechanical Characteristics**

Footprint/Type:	Keystone
Plug /Jack Compatibility:	RJ45
Termination Type:	Universal T568A/B

## Standards

Data Category:	Category 6A
TIA/EIA Compliance:	ISO/IEC 11801-1:2017(Ed.3) ; TIA 568-C.3; EN 50173:2018

## Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU Directive 2011/65/EU (RoHS 2):	Yes
MII Order #39 (China RoHS):	EUP 50

## Part Number

Related Parts:	PatchPro Connectivity, 10GX JACK UTP PPRO PC 10GX UTP LSZH, Upgrade RFID kit
----------------	--

## Variants

Item #	Color
PPC6AUR	NN

## History

Update and Revision:	Revision Number: 0.48 Revision Date: 07-20-2021
----------------------	---

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.