



Product: [RJ45 G-RJ45 G-1032](#) 

Gigabit Ethernet Cat7 Data Double-Ended Cordset: Male straight RJ45 to male straight RJ45, shielded, 50 V AC / 60 V DC, 0.5 A; X-TPE green cable, 8-wires, 4x2x0.14 mm²

Product Description

Gigabit Ethernet Cat7 Data Double-Ended Cordset: Female straight wall mounting X-coded black M12 to male straight RJ45, shielded, 50 V AC / 60 V DC, 0.5 A; X-TPE green cable, 8-wires, 4x2x0.14 mm²

Technical Specifications

Face View Side 1

Pin 1	Pin 2	Pin 3	Pin 4	Pin 5	Pin 6	Pin 7	Pin 8
white	orange	white	green	white	brown	white	blue

Face View Side 2

Pin 1	Pin 2	Pin 3	Pin 4	Pin 5	Pin 6	Pin 7	Pin 8
white	orange	white	blue	white	green	white	brown

Product Description

Brand:	Lumberg Automation
Connector Type:	Cordset, double ended
Shielding:	Shielded
Rated Voltage:	60 V
Rated Impulse Voltage:	0.8 kV
Rated Current*:	0.5 A
Data Transmission:	Gigabit Ethernet Cat7
Data Transmission Rate:	10 Gbit/s

Technical Data Side 1

Product Sub Family:	RJ45
Connector Design:	Straight
Attachment Type:	RJ45
Number of Pins:	8
Coding:	RJ45
Contact Resistance:	≤ 10 mOhm
Insulation Resistance:	> 10 ⁹ Ohm
Mating Cycles:	≤ 100
Ambient Temperature (Operation)*:	- 40 °C - + 70 °C
Protection Degree / IP Rating**:	IP20
Design Standard:	IEC 61076-2-109
Pollution Degree:	4 acc. to DIN EN 60664-1 (VDE 0110-1)
Contact Base Material:	CuSnP
Contact Plating:	AuNi
Contact Bearer Material:	PC
Contact Bearer Color:	Clear
Flammability Class (Contact Bearer):	UL 94 V-0
Molded Body Material:	TPU

Molded Body Color:	Black
Attachment Material:	PC
Attachment Plating:	Nickel-plated
Shielding Material:	GD-Zn, nickel-plated

Cable Data

Cable Number:	1032
Conductor Size:	26 AWG
Number of Wires:	8
Conductor material:	Cu
Cable Jacket Material:	TPE
Cable Jacket Color:	Green
Cable Diameter D:	ø 6.80 ± 0.20 mm
Insulated Wire Diameter:	ø 1.05 ± 0.05 mm
Overall Shield (Cable):	Cu-ETP1 tinned
Ambient Temperature (Fixed Installation):	- 40 °C - + 70 °C
Ambient Temperature (Flex Installation):	- 40 °C - + 70 °C
Flammability Class (Cable Jacket):	IEC 60332-1-2
Core Colors:	white & blue, white & orange, white & green, white & brown

Technical Data Side 2

Product Sub Family, Side 2:	RJ45
Connector Design, Side 2:	Straight
Attachment Type, Side 2:	RJ45
Number of Pins, Side 2:	8
Coding, Side 2:	RJ45
Contact Resistance, Side 2:	≤ 20 mOhm
Insulation Resistance, Side 2:	> 10 ⁹ Ohm
Mating Cycles, Side 2:	≤ 750
Ambient Temperature (Operation), Side 2*:	- 40 °C - + 70 °C
Protection Degree / IP Rating, Side 2**:	IP20
Design Standard, Side 2:	IEC 60603-7
Pollution Degree, Side 2:	3 acc. to DIN EN 60664-1 (VDE 0110-1)
Overvoltage Category, Side 2:	I acc. to DIN EN 60664-1 (VDE 0110-1)
Contact Base Material, Side 2:	CuSnP
Contact Plating, Side 2:	AuNi
Contact Bearer Material, Side 2:	PC
Contact Bearer Color, Side 2:	Clear
Molded Body Material, Side 2:	TPE
Molded Body Color, Side 2:	Black
Attachment Material, Side 2:	PC
Attachment Plating, Side 2:	Nickel-plated
Shielding Material, Side 2:	CuZn, tin-plated

Safety & Environmental Compliance

RoHS Compliant:	yes
-----------------	-----

Resistances

Rail:	No
Oil Resistance:	IEC 60811-2-1

Notes

Note Derating:	Notice derating
----------------	-----------------

History

Update and Revision:	Revision Number: 0.6 Revision Date: 01-14-2025
----------------------	--

Variants

Item #	Item Description
900016510	RJ45 G-RJ45 G-1032/1M
900016511	RJ45 G-RJ45 G-1032/2M
900016512	RJ45 G-RJ45 G-1032/3M
900016513	RJ45 G-RJ45 G-1032/4M
900016514	RJ45 G-RJ45 G-1032/5M
900016509	RJ45 G-RJ45 G-1032/0.5M

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.