



Product: [RS 190M-669](#)

Life Cycle Status: Obsolete


Replaced by: [RS 190M-769](#)

Obsolete | Replacement: RS 190M-769

Product Description

Singled-Ended Cordset| 1-1/8"- Male Straight | #Contacts: 19 | 300 V / 8 & 3 A | Cable PUR Yellow; 19x18 AWG; NUMERIC | cURus 2238

Technical Drawing



Technical Specifications

Face View

Pin 1	Pin 2	Pin 3	Pin 4	Pin 5	Pin 6	Pin 7	Pin 8	Pin 9	Pin 10	Pin 11	Pin 12	Pin 13	Pin 14	Pin 15	Pin 16	Pin 17	Pin 18	Pin 19
black 1	black 2	black 3	black 4	black 5	black 6	black 7	black 8	black 9	black 10	black 11	green-yellow	black 13	black 14	black 15	black 16	black 17	black 18	black 19

Technical Data

Product Family:	Power Connector
Side 1 Product Sub Family:	1-1/8" (9; 10; 12; 19 contacts)
Brand:	Lumberg Automation
Connector Type:	Cordset, single ended
Side 1 Type of Contact/Gender:	Socket Contacts / Female
Connector Design:	1-1/8" Male 19 Pole 0°
Number of Pins:	19 (18+PE)
Coding, Side 1:	A
Shielding Type:	Unshielded
Attachment Type:	Male Thread (coupling screw)
Voltage Rating:	300 V
Rated Voltage (UL):	300 V
Operating Voltage:	270 V
Rated Current (UL)*:	Power 8 A Signal 3 A

Mating Cycles:	≤ 50
Ambient Temperature (Operation)*:	- 40 °C to + 90°C
Protection Degree / IP Rating**:	IP65, IP67, NEMA 6P
Side 1 Pollution Degree:	3 acc. to DIN EN 60664-1 (VDE 0110-1)

Materials

Contact Base Material:	Brass (CuZn)
Side 1 Contact Plating:	Gold / Silver alloy (Au / Ag)
Contact Bearer Material:	Thermoplastic polyurethane (TPU)
Contact Bearer Color:	Yellow
Flammability Class (Contact Bearer):	UL 94 HB
Molded Body Material:	Thermoplastic polyurethane (TPU)
Molded Body Color:	Yellow
Flammability Class (Molded Body):	UL 94 HB
Attachment Material:	Aluminum (Al)
Attachment Plating:	Anodized; Black

Additional Technical Data

Fastening Torque (Attachment):	1-1/8": 70 Ncm, hand-tight
--------------------------------	----------------------------

Cable Data

Cable Number:	669
Conductor Size:	18 AWG
Number of Wires:	19
Minimal Bending Radius (Flexible Inst):	> 10 x D
Cycles (Bending):	> 5 Mio.
Conductor Material:	Cu
Cable Jacket Material:	Polyurethane (PUR)
Cable Jacket Color:	Yellow
Cable Diameter D:	Ø 12.4 mm
Wire Insulation Material:	Polyvinyl Chloride w/ Nylon (PVC-Nylon)
Insulated Wire Diameter:	Ø 2.00 mm
Ambient Temperature (Fixed Installation):	- 40 °C to + 90°C
UL Cable Type:	AWM 20233
Flammability Class (Cable Jacket):	FT1
Cable Characteristics:	Flexibility: Excellent Abrasion Resistance: Excellent Oil & Chemical Resistance: Excellent UV Resistance: Good to excellent Low Temp Performance: Excellent (flexible to -25°C) Flame Retardance: Varies Halogen-Free: Yes Mechanical Durability: High (resists impact; tear; and flex) Environmental Suitability: Outdoor; oily; wet; or rough environments

Approvals

UL-File:	E315587
UL:	UL 2238; cURus

Safety & Environmental Compliance

RoHS Compliant:	Yes
-----------------	-----

Notes

Note Derating:	* Notice derating
Protection Degree / IP Rating Note:	IP Rating tested according to IEC standard using combination of a Hirschmann or Lumberg Automation connector mounted and locked

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.