

# Product: <u>RSMGVS-8M-998</u> ☑

SPE single ended cordset: M8 male straight 6P-M8 Code, IP65/67, PUR



# **Product Description**

SPE single ended cordset: M8 male straight 6P-M8 Code, IP65/67, PUR

# **Technical Specifications**

Face View Side 1

Pin 1 Pin 2 Blue Natural White

# **Product Description**

| Product Family:      | SPE Cordset                              |
|----------------------|--|
| Brand:               | Lumberg Automation                       |
| Connector Type:      | Cordset, single ended                    |
| Shielding:           | Shielded                                 |
| Rated Voltage:       | 60 V                                     |
| Rated Voltage (UL):  | 60 V AC/DC                               |
| Operating Voltage:   | 50 V AC / 60 V DC                        |
| Rated Current*:      | 4 A                                      |
| Rated Current (UL)*: | 4 A                                      |
| Data Transmission:   | 1 Gbit/s bis 40 m / 10 Mbit/s bis 1000 m |

# Technical Data Side 1

| SPE Cordset M8 (T1 Industrial)        |
|---------------------------------------|
| Male                                  |
| Straight                              |
| Screw-Locking                         |
| 2                                     |
| ≤ 10 mOhm                             |
| > 5x10^8 Ohm                          |
| ≤ 100                                 |
| - 40 °C - + 90 °C (Cable +80 °C)      |
| max. + 85 °C                          |
| IP65, IP67                            |
| IEC 63171-6                           |
| 3 acc. to DIN EN 60664-1 (VDE 0110-1) |
| DIN EN 60664-1 (2008/01); VDE 0110-1  |
| CuSn                                  |
| Cu/Au                                 |
| PA                                    |
| Black                                 |
| UL 94 V-0                             |
| TPU                                   |
|                                       |

| Molded Body Color:                | Black                     |
|-----------------------------------|---------------------------|
| Flammability Class (Molded Body): | UL 94 V-0                 |
| Attachment Material:              | CuZn                      |
| Attachment Plating:               | Nickel-plated             |
| Fastening Torque (Attachment):    | M 8x1: 40 Ncm, hand-tight |

#### **Cable Data**

| Cable Number:                             | 998                              |
|---|----------------------------------|
| Number of Wires:                          | 2                                |
| Conductor material:                       | Cu                               |
| Cable Jacket Material:                    | PUR                              |
| Cable Jacket Color:                       | blue                             |
| Cable Diameter D:                         | ø 5.50 ± 0.20 mm                 |
| Wire Insulation Material:                 | PE                               |
| Insulated Wire Diameter:                  | ø 1,9 ±0.1 mm                    |
| Overall Shield (Cable):                   | Tinned copper                    |
| Foil shield:                              | Al-myler wrapping foil           |
| Ambient Temperature (Fixed Installation): | - 40 °C - +80 °C                 |
| UL Cable Type:                            | AWM: 20549                       |
| Flammability Class (Cable Jacket):        | FT-2                             |
| Cable Characteristics:                    | Exclusion of dangerous materials |

#### **Approvals**

| UL: | UL 2238; cULus |
|-----|----------------|

# Safety & Environmental Compliance

| RoHS Compliant: | Yes |
|-----------------|-----|
| Notes           |     |

Revision Number: 0.27 Revision Date: 02-01-2024

| Note Derating: | Notice derating |
|----------------|-----------------|
|                |                 |

# History

| Update and Revision: |
|----------------------|
|----------------------|

### Variants

| Item #    | Item Description   | Cable Length |
|-----------|--------------------|--------------|
| 935100023 | RSMGVS-8M-998/1 M  | 1 m          |
| 935100025 | RSMGVS-8M-998/2 M  | 2 m          |
| 935100028 | RSMGVS-8M-998/5 M  | 5 m          |
| 935100021 | RSMGVS-8M-998/10 M | 10 m         |
| 935100022 | RSMGVS-8M-998/15 M | 15 m         |
| 935100024 | RSMGVS-8M-998/20 M | 20 m         |
| 935100026 | RSMGVS-8M-998/30 M | 30 m         |
| 935100027 | RSMGVS-8M-998/40 M | 40 m         |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.