



Product: [UTG1CUP](#)

UTG 10 CABLE, 4PR U/UTP, CMP, 23 AWG

Product Description

UTG 10 PREMISE HORIZONTAL CABLE (425 MHz), 4PR U/UTP, CMP, 23 AWG SOLID CONDUCTORS

Technical Specifications

Product Overview

Suitable Applications:	Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155 ATM, 622 ATM, 4K UHD Video Surveillance, PoE Type 4 (100W), 4K UHD HDBaseT, PoH, WiFi (IEEE 802.11ax)
Patent:	This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/patents .

Physical Characteristics (Overall)

Conductor			
AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4
Conductor Count:			8
Total Number of Pairs:			4

Insulation	
Material	
PO+FEP - Polyolefin + Fluorinated Ethylene Propylene	
Bonded-Pair:	N/A

Color Chart	
Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Outer Jacket			
Material	Material Trade Name	Nominal Diameter	Ripcord
PVC - Polyvinyl Chloride	Flamarrest®	0.224 in	Yes

Electrical Characteristics

Conductor DCR	
Max. Conductor DCR	Max. DCR Unbalance
78 Ohm/km	3.0 %

Capacitance	
Max. Capacitance Unbalance	Nom.Mutual Capacitance
330 pF/100m	17 pF/ft

Delay		
Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
537.6 ns/100m	35 ns/100m	72%

High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance
1 MHz	2.0 dB/100m	75.3 dB	75.3 dB	73.3 dB	73.3 dB	70.8 dB	67.8 dB	20.0 dB	100 ± 15 Ohm	102 ± 15 Ohm
4 MHz	3.7 dB/100m	66.3 dB	66.3 dB	62.6 dB	62.6 dB	58.8 dB	55.8 dB	23.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
8 MHz	5.2 dB/100m	61.8 dB	61.8 dB	56.6 dB	56.6 dB	52.7 dB	49.7 dB	24.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
10 MHz	5.8 dB/100m	60.3 dB	60.3 dB	54.5 dB	54.5 dB	50.8 dB	47.8 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
16 MHz	7.4 dB/100m	57.2 dB	57.2 dB	49.9 dB	49.9 dB	46.7 dB	43.7 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
20 MHz	8.3 dB/100m	55.8 dB	55.8 dB	47.5 dB	47.5 dB	44.8 dB	41.8 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm
25 MHz	9.3 dB/100m	54.3 dB	54.3 dB	45.1 dB	45.1 dB	42.8 dB	39.8 dB	24.3 dB	100 ± 15 Ohm	100 ± 15 Ohm
31.25 MHz	10.4 dB/100m	52.9 dB	52.9 dB	42.5 dB	42.5 dB	40.9 dB	37.9 dB	23.6 dB	100 ± 15 Ohm	100 ± 15 Ohm
62.5 MHz	15.0 dB/100m	48.4 dB	48.4 dB	33.4 dB	33.4 dB	34.9 dB	31.9 dB	21.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
100 MHz	19.3 dB/100m	45.3 dB	45.3 dB	26.0 dB	26.0 dB	30.8 dB	27.8 dB	20.8 dB	100 ± 15 Ohm	100 ± 15 Ohm
155 MHz	24.6 dB/100m	42.4 dB	42.4 dB	17.9 dB	17.9 dB	27.0 dB	24.0 dB	19.5 dB	100 ± 22 Ohm	100 ± 15 Ohm
200 MHz	28.3 dB/100m	40.8 dB	40.8 dB	12.5 dB	12.5 dB	24.8 dB	21.8 dB	18.7 dB	100 ± 22 Ohm	100 ± 15 Ohm
250 MHz	32.1 dB/100m	39.3 dB	39.3 dB	7.2 dB	7.2 dB	22.8 dB	19.8 dB	18.0 dB	100 ± 32 Ohm	100 ± 15 Ohm
300 MHz	35.6 dB/100m	38.1 dB	36.1 dB	2.5 dB	0.5 dB	21.3 dB	18.3 dB	17.5 dB	100 ± 32 Ohm	100 ± 15 Ohm
350 MHz	38.9 dB/100m	37.1 dB	35.1 dB	-1.8 dB	-3.8 dB	19.9 dB	16.9 dB	17.0 dB	100 ± 32 Ohm	100 ± 15 Ohm
400 MHz	42.0 dB/100m	36.3 dB	34.3 dB	-5.7 dB	-7.7 dB	18.8 dB	15.8 dB	16.6 dB	100 ± 32 Ohm	100 ± 15 Ohm
450 MHz	45.0 dB/100m	35.5 dB	33.5 dB	-9.5 dB	-11.5 dB	17.7 dB	14.7 dB	16.2 dB	100 ± 32 Ohm	100 ± 15 Ohm
500 MHz	47.9 dB/100m	34.8 dB	32.8 dB	-13.1 dB	-15.1 dB	16.8 dB	13.8 dB	15.9 dB	100 ± 32 Ohm	100 ± 15 Ohm
550 MHz	50.6 dB/100m	34.2 dB	32.2 dB	-16.4 dB	-18.4 dB	16.0 dB	13.0 dB	15.6 dB	100 ± 32 Ohm	100 ± 15 Ohm

Voltage

UL Voltage Rating
300 V RMS

Temperature Range

Installation Temperature Range:	0°C To +50°C
UL Temp Rating:	90°C
Storage Temperature Range:	-20°C To +75°C
Operating Temperature Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	26 lbs/1000ft
Max. Pull Tension:	25 lbs
Min. Bend Radius/Minor Axis:	1.0 in

Standards

NEC/(UL) Compliance:	CMP 90C, CMP-LP (0.5A), CL3P-LP (0.5A)
CEC/C(UL) Compliance:	CMP
CPR Euroclass:	Eca
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
Third Party Performance Verification:	UTG Framework 1.0

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
EU REACH SVHC Compliance (yyyy-mm-dd):	2017-07-10

Suitability

Suitability - Aerial:	No
Suitability - Burial:	No

Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	No
Suitability - Oil Resistance:	No
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262 Plenum (UL 910)
IEC Flammability:	IEC 60332-1-2

Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

Related Part Numbers

Non-Plenum Number:	UTG1CUR
--------------------	---------

Product Notes

Notes:	Values above 350 MHz are for Engineering Information Only. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0.
--------	---

History

Update and Revision:	Revision Number: 0.55 Revision Date: 12-12-2023
----------------------	---

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.