



Product: XSW-8419 ☑

Belden Swing Rack

Product Description

Free Standing Swing-Out Rack used where space is limited

Technical Specifications

Application

| Product Overview: | The Swing Rack provides easy access to the rear of rack-mounted equipment in a free standing environment. It is ideal for applications where space is limited and rear access is essential. Rack can be assembled as a left or right hinge and open 90 degrees. Rack can be positioned as close as 7" from wall. Equipment up to 18.5" deep can be pivoted. Cable management allows for cable routing without interference of the swing rack. Racks can be bolted side-to-side. Friction lock prevents rack movement while servicing. |
|----------------------|---|
| Features: | Rack can be assembled as a left or right hinge and open 90°, Rack can be positioned as close as 7" from wall, Equipment up to 18.5" deep can be pivoted, Cable management allows for cable routing without interference of the swing rack, Racks can be bolted side-to-side, Friction lock prevents rack movement while servicing |
| Environmental Space: | Indoor |

Construction and Dimensions

| Construction: | Steel |
|---------------|--------|
| Rack Units: | 43U |
| Width: | 34.375 |
| Depth: | 15.0 |

Mechanical Characteristics

| Mounting: | 19 in |
|----------------|--------|
| Load Capacity: | 500 lb |
| Rail Tapping: | 10-32 |

Environmental and Overall Characteristics

| Finish: | Black Powdercoat Finish |
|-----------|-------------------------|
| Material: | Steel |
| Color: | Black |
| Weight: | 200.0 |

Related Part Numbers

| Part Number: | XSW-8419 |
|--------------|------------------|
| Packaging: | Individual Boxed |

Variants

| Part # | Mounting | Width | Rail Tapping | Load Capacity | Rack Spaces | Weight |
|----------------------|----------|-------------|-------------------|-------------------|-------------|--------|
| XSW-8419 | 19 in | 34.375 in | 10-32 | 500 lb | 43U | 200 lb |
| Update and Revision: | Rev | ision Numbe | er: 0.60 Revision | n Date: 11-14-202 | 22 | |

© 2024 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.