


Product: [YE03414](#) 



5X COAX MINI RG59/U QUAD SHIELD PVC HEAD END

Product Description

5X COAX [0.58/2.6] MINI RG59U/ QUAD SHIELD PVC HEAD END

Technical Specifications

Product Overview

Suitable Applications:	Mini RG59 quad shield coaxial cable used where immunity to conducted disturbances is required, but space is limited; Coaxial cable used in cable broadband communication networks designed according European Standard EN 50117-1; Operating frequencies between 5 and 3000 MHz
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
23	Solid	BC - Bare Copper	0.58 mm	0.02 mm	5

Conductor Count: 5

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene (Foam)	2.59 mm	0.15 mm

Color Chart

Color
Violet
Orange
Brown
Black
Gray

Inner Shield

Type	Layer	Material	Coverage [%]	Min. Overlap	Coverage +/- Tolerance
Tape	1	Tri-Laminate (Alum+Poly+Alum)		2 mm	
Braid	2	Tinned Copper (TC)	95%		5%
Tape	3	Tri-Laminate (Alum+Poly+Alum)		1 mm	
Braid	4	Tinned Copper (TC)	90%		5%

Inner Jacket

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	4.7 mm	0.23 mm

Outer Jacket

Material	Nominal Diameter
PVC - Polyvinyl Chloride	14.5 mm

Construction and Dimensions

Cabling

Description	Filler

5 coax bundled around a filler covered with nonwoven foil Polypropylene (1x)

Min Elongation at Breakof Jacket:	150 %
Min Tensile Strength of Jacket:	12.5 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
66 Ohm/km	75 Ohm/1000ft	6.5 Ohm/km

Capacitance

Nom. Capacitance	Capacitance Tolerance
53 pF/m	2 pF/m

Min Insulation Resistance: 10000 MOhm*km

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
75 Ohm	3 Ohm	Min. 40 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	1.7 dB/100m
3.6 MHz	2.6 dB/100m
10 MHz	3.9 dB/100m
71.5 MHz	10 dB/100m
135 MHz	12.5 dB/100m
270 MHz	17.7 dB/100m
540 MHz	25.3 dB/100m
720 MHz	31.1 dB/100m
750 MHz	31.5 dB/100m
1000 MHz	34.4 dB/100m
1500 MHz	42.7 dB/100m
2000 MHz	52 dB/100m
2250 MHz	52.5 dB/100m
3000 MHz	60.7 dB/100m

Table Notes: Max. attenuation 10% higher

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
400 ns/ft	83%	2%

High Frequency

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 30 MHz	23 dB
30 - 850 MHz	23 dB
850 - 3000 MHz	21 dB

Table Notes: In each frequency band, 3 peak values up to 4 dB lower are allowed

Screening

Frequency [MHz]	Min. Screening Attenuation After Flexing
30 - 1000 MHz	110 dB
1000 - 2000 MHz	95 dB
2000 - 3000 MHz	85 dB

Screening Class: A++

Transfer Impedance

Frequency [MHz]	Transfer Impedance
5-30 MHz	Max. 0.9 mOhm/m

Temperature Range

Installation Temperature Range: -5°C To +50°C

Storage Temperature Range:	-40°C To +70°C
Operating Temperature Range:	-40°C To +70°C

Mechanical Characteristics

Max. Pull Tension:	160 N
Min Bend Radius (W/o Pulling Strength):	150 mm
Min Bend Radius (Each Coax):	47 mm

Standards

GENELEC Compliance:	EN 50117-1, EN 50117-9-2, EN 50290-2-20
RG Type:	Mini 59

Applicable Environmental and Other Programs

Environmental Space:	Indoor/Outdoor
----------------------	----------------

Flammability, LSOH, Toxicity Testing

CSA Flammability:	FT4
IEC Flammability:	IEC 60332-3-24

Related Part Numbers

Variants

Item #	Color	Put-Up Type	Length	EAN
YE03414.00500	Black	Reel	500 m	8719605118424

History

Update and Revision:	Revision Number: 0.145 Revision Date: 05-31-2024
----------------------	--

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.