


Product: [YE03417](#) 



10X COAX MINI RG59 dBII HEAD END

Product Description

10X COAX MINI RG59 dBII HEAD END

Technical Specifications

Product Overview

| | |
|------------------------|---|
| Suitable Applications: | Mini RG59 tri shield coaxial cable used where immunity space is limited; Coaxial cable used in cable broadband communication networks designed according European Standard EN 50117-1; Operating frequencies between 5 and 3000 MHz |
|------------------------|---|

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | Nominal Diameter | Diameter +/- Tolerance | No. of Coax |
|-----|-----------|------------------|------------------|------------------------|-------------|
| 23 | Solid | BC - Bare Copper | 0.58 mm | 0.02 mm | 10 |

Conductor Count: 10

Insulation

| Type | Material | Nominal Diameter | Diameter +/- Tolerance |
|------------|--------------------------|------------------|------------------------|
| Dielectric | PE - Polyethylene (Foam) | 2.59 mm | 0.15 mm |

Color Chart

| Number | Color |
|--------|--------|
| 1 | Red |
| 2 | Green |
| 3 | Blue |
| 4 | White |
| 5 | Yellow |
| 6 | Brown |
| 7 | Orange |
| 8 | Gray |
| 9 | Violet |
| 10 | Black |

Inner Shield

| Type | Layer | Material | Coverage [%] | Min. Overlap | Coverage +/- Tolerance |
|-------|-------|-------------------------------|--------------|--------------|------------------------|
| Tape | 1 | Tri-Laminate (Alum+Poly+Alum) | | 2 mm | |
| Braid | 2 | Tinned Copper (TC) | 95% | | 5% |

Inner Jacket

| Material | Nominal Diameter | Diameter +/- Tolerance |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 4 mm | 0.23 mm |

Outer Jacket

| Material | Nominal Diameter |
|--------------------------|------------------|
| PVC - Polyvinyl Chloride | 18.1 mm |

Construction and Dimensions

Cabling

| Description | Filler |
|---|--------------------|
| 8 coax + 2 fillers bundled around 2 coax and 2 fillers covered with nonwoven foil | Polypropylene (4x) |

| | |
|-----------------------------------|----------|
| Min Elongation at Breakof Jacket: | 150 % |
| Min Tensile Strength of Jacket: | 12.5 MPa |

Electrical Characteristics

Conductor DCR

| Max. Conductor DCR | Max. Conductor Loop | Max. Shield DCR |
|--------------------|---------------------|-----------------|
| 66 Ohm/km | 83 Ohm/1000ft | 17 Ohm/km |

Capacitance

| Nom. Capacitance | Capacitance Tolerance |
|------------------|-----------------------|
| 53 pF/m | 2 pF/m |

| | |
|----------------------------|---------------|
| Min Insulation Resistance: | 10000 MOhm*km |
|----------------------------|---------------|

Impedance

| Nominal Characteristic Impedance | Nominal Characteristic Tolerance | Regularity of Impedance |
|----------------------------------|----------------------------------|-------------------------|
| 75 Ohm | 3 Ohm | Min. 40 dB |

High Frequency (Nominal/Typical)

| Frequency [MHz] | Nom. Insertion Loss |
|-----------------|---------------------|
| 1 MHz | 1.7 dB/100m |
| 3.6 MHz | 2.6 dB/100m |
| 10 MHz | 3.9 dB/100m |
| 71.5 MHz | 10 dB/100m |
| 135 MHz | 12.5 dB/100m |
| 270 MHz | 17.7 dB/100m |
| 540 MHz | 25.3 dB/100m |
| 720 MHz | 31.1 dB/100m |
| 750 MHz | 31.5 dB/100m |
| 1000 MHz | 34.4 dB/100m |
| 1500 MHz | 42.7 dB/100m |
| 2000 MHz | 52 dB/100m |
| 2250 MHz | 52.5 dB/100m |
| 3000 MHz | 60.7 dB/100m |
| 4500 MHz | 74.8 dB/100m |

| | |
|--------------|-----------------------------|
| Table Notes: | Max. attenuation 10% higher |
|--------------|-----------------------------|

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] | Velocity of Propagation Tolerance |
|---------------|--|-----------------------------------|
| 400 ns/ft | 83% | 2% |

High Frequency

| Frequency [MHz] | Min. RL (Return Loss) [dB] |
|-----------------|----------------------------|
| 5 - 30 MHz | 23 dB |
| 30 - 1000 MHz | 21 dB |
| 1000 - 3000 MHz | 18 dB |
| 3000 - 4500 MHz | 18 dB |

| | |
|--------------|--|
| Table Notes: | In each frequency band, 3 peak values up to 4 dB lower are allowed |
|--------------|--|

Screening

| Frequency [MHz] | Min. Screening Attenuation After Flexing |
|-----------------|--|
| 30 - 1000 MHz | 75 dB |
| 1000 - 2000 MHz | 65 dB |
| 2000 - 3000 MHz | 55 dB |

| | |
|------------------|---|
| Screening Class: | B |
|------------------|---|

Transfer Impedance

| Frequency [MHz] | Transfer Impedance |
|-----------------|--------------------|
|-----------------|--------------------|

| | |
|----------|----------------|
| 5-30 MHz | Max. 15 mOhm/m |
|----------|----------------|

Temperature Range

| | |
|---------------------------------|----------------|
| Installation Temperature Range: | -5°C To +50°C |
| Storage Temperature Range: | -40°C To +70°C |
| Operating Temperature Range: | -40°C To +70°C |

Mechanical Characteristics

| | |
|---|--------|
| Max. Pull Tension: | 160 N |
| Min Bend Radius (W/o Pulling Strength): | 200 mm |
| Min Bend Radius (Each Coax): | 40 mm |

Standards

| | |
|---------------------|---|
| GENELEC Compliance: | EN 50117-1, EN 50117-9-2, EN 50290-2-20 |
| RG Type: | Mini 59 |

Applicable Environmental and Other Programs

| | |
|----------------------|----------------|
| Environmental Space: | Indoor/Outdoor |
|----------------------|----------------|

Flammability, LSOH, Toxicity Testing

| | |
|-------------------|----------------|
| CSA Flammability: | FT4 |
| IEC Flammability: | IEC 60332-3-24 |

Related Part Numbers

Variants

| Item # | Color | Put-Up Type | Length | EAN |
|---------------|-------|-------------|--------|---------------|
| YE03417.00250 | Black | Reel | 250 m | 8719605118646 |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.144 Revision Date: 05-31-2024 |
|----------------------|--|

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.