



REPRESENTATIVE IMAGE

Product: [XCZ1](#)

Category 3 Cross Connect Cable, 1 Pair, U/UTP, PVC Jacket

Product Description

Category 3 Premise Cross Connect Cable (16MHz), 1 Pair, U/UTP, 24 AWG Solid Bare Copper Conductors, PVC Jacket

Technical Specifications

Product Overview

Suitable Applications:	Cross-Connect, Interconnect
------------------------	-----------------------------

Construction Details

Conductor

Size	Stranding	Material	No. of Pairs
24 AWG	Solid	BC - Bare Copper	1

Insulation

Material
PVC - Polyvinyl Chloride

Table Notes:	Overall Nominal Diameter: 0.072 in
--------------	------------------------------------

Mechanical Characteristics

Temperature

UL Temperature
60°C

Bend Radius

Stationary Min.	Installation Min.
1 in (25 mm)	1 in (25 mm)

Max. Pull Tension:	15 lbs (6.8 kg)
Bulk Cable Weight:	5 lbs/1000ft

Standards and Compliance

Flammability / Reaction to Fire:	UL 1685 (UL Loading)
NEC / UL Compliance:	Cross-Connect
Data Category:	Category 3
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.363 Revision Date: 04-29-2024
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
XCZ1 D921000	Blue/Red and Red/Blue	Reel	1,000 ft	612825060888

XCZ1 D921000	Blue/Red and Red/Blue	Reel	1,000 ft	612825060888
XCZ1 D87500	Blue/White and White/Blue	Reel	500 ft	612825060895
XCZ1 D87500	Blue/White and White/Blue	Reel	500 ft	612825060895
XCZ1 E031000	Blue/Yellow and Yellow/Blue	Reel	1,000 ft	612825060871
XCZ1 E031000	Blue/Yellow and Yellow/Blue	Reel	1,000 ft	612825060871
XCZ1 E031000B	Blue/Yellow and Yellow/Blue	Reel	1,000 ft	
XCZ1 E031000B	Blue/Yellow and Yellow/Blue	Reel	1,000 ft	

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.