



METRIC MEASUREMENT VERSION

## 2103A Multi-Conductor - DataBus® ISA/SP-50 FOUNDATION Fieldbus or PROFIBUS Cable



For more Information  
please call

1-800-Belden1



### General Description:

8 pair, 18 AWG stranded (7x26) tinned copper conductors, XLP insulation, individual and overall Beldfoil® shields (100% coverage), tinned copper drain wire, sunlight- and oil-resistant FR-PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Pairs	AWG	Stranding	Conductor Material
8	18	7x26	TC - Tinned Copper

Total Number of Conductors: 16

#### Insulation

##### Insulation Material:

Insulation Material
XLP - Cross-linked Polyolefin

#### Inner Shield

##### Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

##### Inner Shield Drain Wire AWG:

AWG	Stranding	Conductor Material
20	7x28	TC - Tinned Copper

#### Outer Shield

##### Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

##### Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire	Conductor Material
18	7x26		TC - Tinned Copper

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material
FR PVC - Polyvinyl Chloride

Outer Jacket Ripcord: Yes

#### Overall Cable

Overall Nominal Diameter: 20.320 mm

#### Pair

##### Pair Color Code Chart:

Number	Color
1	Blue & Orange Numbered 1
2	Blue & Orange Numbered 2
3	Blue & Orange Numbered 3
4	Blue & Orange Numbered 4

## 2103A Multi-Conductor - DataBus® ISA/SP-50 FOUNDATION Fieldbus or PROFIBUS Cable

5	Blue & Orange Numbered 5
6	Blue & Orange Numbered 6
7	Blue & Orange Numbered 7
8	Blue & Orange Numbered 8

### Mechanical Characteristics (Overall)

<b>Operating Temperature Range:</b>	-25°C Cold Impact, -40°C To +90°C, -55°C Cold Bend
<b>UL Temperature Rating:</b>	90°C Wet/Dry
<b>Installation Temperature Rating:</b>	-25°C
<b>Bulk Cable Weight:</b>	465.807 Kg/Km
<b>Max. Recommended Pulling Tension:</b>	2139.584 N
<b>Min. Bend Radius/Minor Axis:</b>	203.200 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

<b>NEC/(UL) Specification:</b>	CMG, ITC, PLTC-ER
<b>CSA Specification:</b>	AWM I A/B II A/B, C22.2 #230 Type TC; C22.2#239 Type CIC
<b>EU Directive 2011/65/EU (ROHS II):</b>	Yes
<b>EU CE Mark:</b>	Yes
<b>EU Directive 2000/53/EC (ELV):</b>	Yes
<b>EU Directive 2002/95/EC (RoHS):</b>	Yes
<b>EU Directive 2002/96/EC (WEEE):</b>	Yes
<b>EU Directive 2003/11/EC (BFR):</b>	Yes
<b>CA Prop 65 (CJ for Wire &amp; Cable):</b>	Yes
<b>MII Order #39 (China RoHS):</b>	Yes
<b>Other Specification:</b>	IEC 61158-2 (ISA/SP-50) Type A

#### Flame Test

<b>UL Flame Test:</b>	UL1685 FT4 Loading
<b>CSA Flame Test:</b>	FT4
<b>IEC Flame Test:</b>	60332-3-24 (Category C)

#### Suitability

<b>Suitability - Indoor:</b>	Yes
<b>Suitability - Outdoor:</b>	Yes
<b>Sunlight Resistance:</b>	Yes
<b>Oil Resistance:</b>	Yes

#### Plenum/Non-Plenum

<b>Plenum (Y/N):</b>	No
----------------------	----

### Electrical Characteristics (Overall)

#### Unaveraged Impedance:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Impedance (Ohm)
	.03125			100

#### Nom. Inductance:

<b>Inductance (µH/m)</b>
0.722

#### Nom. Capacitance Conductor to Conductor:

<b>Capacitance (pF/m)</b>
---------------------------

METRIC MEASUREMENT VERSION

## 2103A Multi-Conductor - DataBus® ISA/SP-50 FOUNDATION Fieldbus or PROFIBUS Cable

72.182

**Maximum Capacitance Unbalance:**

Capacitance (pF/m)
3.9372

**Nominal Velocity of Propagation:**

VP (%)
64.000

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/km)
19.2267

**Nom. Attenuation:**

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Attenuation (dB/100m)
	.039			0.26248

**Max. Attenuation:**

()	Freq. (MHz)	Attenuation (dB/100m)
0.298571	0.039	0.299

**Max. Operating Voltage - UL:**

Voltage
300 V RMS

**Max. Operating Voltage - Other:**

Voltage	Description
300V RMS	CSA CIC type TC

**Max. Recommended Current:**

Description	Current
Per Conductor	7.6 Amps

**Other Electrical Characteristic 1:** Max Propagation Delay Change From 7.812 kHz to 39.06 kHz: 518 pS/ft

**Other Electrical Characteristic 2:** 31.25 KBits/sec

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
2103A 0031000	1,000 FT	407.000 LB	ORANGE		300V/PR/08/18AWG/7T/XLPE/ORGBL
2103A 0035000	5,000 FT	1,840.000 LB	ORANGE		300V/PR/08/18AWG/7T/XLPE/ORGBL
2103A 0061000	1,000 FT	407.000 LB	BLUE, LIGHT		300V/PR/08/18AWG/7T/XLPE/ORGBL
2103A 0065000	5,000 FT	1,840.000 LB	BLUE, LIGHT		300V/PR/08/18AWG/7T/XLPE/ORGBL

Revision Number: 1    Revision Date: 09-29-2014

© 2019 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).