

## 27276 Multi-Conductor - 600V Type MC Metal Clad Cable



For more Information  
please call

1-800-Belden1

**General Description:**

12 AWG stranded (7x20) bare copper conductors, 12 AWG bare copper ground wire, e cross-linked polyethylene insulation, aluminum interlocked armor, PVC jacket.

**Physical Characteristics (Overall)****Conductor****AWG:**

# Conductors	AWG	Stranding	Conductor Material
12	12	7x20	BC - Bare Copper

Total Number of Conductors: 12

**Ground Wire**

Ground Wire (Y/N): Y

Ground Wire AWG: 12

Ground Wire Stranding: 7x20

Ground Wire Conductor Material: BC - Bare Copper

**Insulation****Insulation Material:**

Insulation Material	Wall Thickness (mm)
XLPE - Cross Linked Polyethylene	0.762

**Outer Shield****Outer Shield Material:**

Outer Shield Material
Unshielded

**Outer Jacket**

Outer Jacket over Armor (y/n): Y

**Outer Jacket over Armor**

Outer Jacket Material over Armor (y/n): PVC

Outer Jacket Wall Thickness Over Armor: .050

**Armor**

Armor Type: Interlocked

Armor Material: Aluminum

Diameter over Armor: .84

**Overall Cable****Overall Cabling Color Code Chart:**

Number	Color
1	Black
2	Red
3	Blue
4	Orange
5	Yellow
6	Brown
7	Red/Black

## 27276 Multi-Conductor - 600V Type MC Metal Clad Cable

8	Blue/Black
9	Orange/Black
10	Yellow/Black
11	Brown/Black
12	Black/Red

Overall Nominal Diameter: 23.876 mm

**Mechanical Characteristics (Overall)**

Operating Temperature Range:	-40°C To +90°C
Wet Temperature Range:	-40°C To +90°C
Dry Temperature Range:	-40°C To +90°C
Bulk Cable Weight:	799.163 Kg/Km
Max. Recommended Pulling Tension:	2753.440 N
Min. Bend Radius/Minor Axis:	297.180 mm

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	MC, XHHW-2 Singles, UL1569
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/13/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

**Flame Test**

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

**Suitability**

Suitability - Burial:	Yes
Sunlight Resistance:	Yes

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

**Electrical Characteristics (Overall)****Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/km)
5.41365

**Max. Operating Voltage - UL:**

Voltage
600 V RMS

**Max. Recommended Current:**

Current
10 Amps per conductor @ 25°C

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

## 27276 Multi-Conductor - 600V Type MC Metal Clad Cable

Revision Number: 1    Revision Date: 03-10-2009

© 2019 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.