



For more Information
please call

1-800-Belden1



General Description:

16 AWG stranded (7x24) bare copper conductors, 16 AWG bare copper ground wire, aluminum interlocked armor, .030x1A; (.76mm) XLPE insulation, PVC inner jacket, PVC outer jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
3	16	7x24	BC - Bare Copper

Total Number of Conductors: 3

Ground Wire

Ground Wire (Y/N): Y

Ground Wire AWG: 16

Ground Wire Stranding: 7x24

Ground Wire Conductor Material: BC - Bare Copper

Insulation

Insulation Material:

Insulation Material
XLPE - Cross Linked Polyethylene

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (mm)
9.144

Outer Jacket over Armor (y/n): Y

Outer Jacket over Armor

Outer Jacket Material over Armor (y/n): PVC - Polyvinyl Chloride

Armor

Armor Type: Interlocked

Armor Material: Aluminum

Diameter over Armor: .56

Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	White and Numbered 1

2	Black and Numbered 2
3	Black and Numbered 3

Overall Nominal Diameter: 16.764 mm

Mechanical Characteristics (Overall)

Wet Temperature Range:	-40°C To +90°C
Dry Temperature Range:	-40°C To +90°C
Non-UL Temperature Rating:	90°C Wet/Dry
Bulk Cable Weight:	328.892 Kg/Km
Max. Recommended Pulling Tension:	293.581 N
Min. Bend Radius/Minor Axis:	200.660 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

CSA Specification:	C22.2#239, HAZ LOC, C22.2#0.3 Clause 4.31 Low Acid Gas
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

Flame Test

CSA Flame Test:	FT4
-----------------	-----

Suitability

Suitability - Burial:	Yes
Sunlight Resistance:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
13.7802

Max. Operating Voltage - Non-UL:

Voltage
600 V RMS

Max. Recommended Current:

Current
10 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

29004 Multi-Conductor - 600V ACIC Cable

Revision Number: 1 Revision Date: 05-14-2007

© 2019 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.