



3078F Multi-Conductor - DataBus® ISA/SP-50 FOUNDATION Fieldbus Cable



For more Information
please call

1-800-Belden1



General Description:

22 AWG stranded (7x30) tinned copper conductors, FHDPE insulation, Beldfoil® shield (100% coverage), tinned copper drain wire, PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
1	22	7x30	TC - Tinned Copper	0.762

Total Number of Conductors: 2

Insulation

Insulation Material:

Insulation Material
FHDPE - Foam High Density Polyethylene

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 8.915 mm

Pair

Pair Color Code Chart:

Number	Color
1	Blue & Orange

Pair Lay Length & Direction:

Lay Length (mm)
101.6

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 59.528 Kg/Km

Max. Recommended Pulling Tension: 142.342 N

Min. Bend Radius/Minor Axis: 88.900 mm

3078F Multi-Conductor - DataBus® ISA/SP-50 FOUNDATION Fieldbus Cable

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

CEC/C(UL) Specification:	CM
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Surface Printing (Overall)

Surface Printing:	BELDEN 3078F DATABUS(R) 1PR22 SHIELDED (UL) CM 75C E108998 OR PLC SUN RES OR C(UL) CM 75C
-------------------	---

Electrical Characteristics (Overall)

Unaveraged Impedance:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Impedance (Ohm)
	1.0			150

Nom. Inductance:

Inductance (µH/m)	0.9843
-------------------	--------

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)	52.496
--------------------	--------

Nom. Mutual Capacitance:

Capacitance (pF/m)	27.8885
--------------------	---------

Maximum Capacitance Unbalance:

Capacitance (pF/m)	1.50926
--------------------	---------

Nominal Velocity of Propagation:

VP (%)	78
--------	----

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)	56.1051
---------------------	---------

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 10.827 Ohm/km

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
.25	0.59058
.625	0.85306

METRIC MEASUREMENT VERSION

3078F Multi-Conductor - DataBus® ISA/SP-50 FOUNDATION Fieldbus Cable

1.25	1.11554
3.125	1.80455

Max. Attenuation:

()	Freq. (MHz)
1.00071	.625
1.29928	1.25
2.00141	3.125

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Recommended Current:

Description	Current
Per Conductor	2.5 Amps

Other Electrical Characteristic 1: ISA/IEC SP50 Requirements: Impedance @ 250 kHz, 625 kHz, 1.25 MHz, and 3.125 MHz: 150 +/- 10% Ohms

Other Electrical Characteristic 2: 1.0 and 2.5 Mbits/sec

Notes (Overall)

Notes: Tape around pair has shorting fold. CPE & LSOH Jacket optional.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
3078F 0031000	1,000 FT	47.000 LB	ORANGE	C	#22 PR FPE/LDPE FS PVC
3078F 0032500	2,500 FT	122.500 LB	ORANGE	C	#22 PR FPE/LDPE FS PVC
3078F 003500	500 FT	24.500 LB	ORANGE	C	#22 PR FPE/LDPE FS PVC

Notes:
C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 09-19-2008

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).