

558AFS Composite - Lock Power, Card Reader, Door Contact, REX Applications

For more Information
please call

1-800-Belden1



General Description:

Access Control Cable, Riser-CMR, 3-22 AWG pairs, 4-18 AWG conductors, 4-22 AWG conductors, 2-22 AWG conductors, All conductors stranded bare copper with polyolefin insulation, Each cable has overall Beldfoil® shield and PVC jacket, Banana Peel® No overall jacket

Usage (Overall)

Suitable Applications: Access Control

Twisted Pair

Physical Characteristics

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
3	22	7x30	BC - Bare Copper

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PP - Polypropylene	0.178

Inner Jacket

Inner Jacket Color Code Chart:

Number	Color
Card Reader 1	Black and Red
Card Reader 2	White and Green
Card Reader 3	Orange and Brown

Individual Shield

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	(7x32)	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
F-R PVC - Flame Retardant Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (mm)
5.359

Outer Jacket Ripcord: Yes

Outer Jacket Color Code Chart:

Number	Color
Card Reader	Orange

558AFS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

NEC Articles: 800

CEC/C(UL) Specification: CMG

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)

147.645

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

82.025

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

53.480

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 45.606 Ohm/km

Max. Operating Voltage - UL:

Description

300 V RMS

Max. Recommended Current:

Description Current

Card Reader 2 amps @ 25C ambient

Multi Conductor

Physical Characteristics

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
2	22	7x30	BC - Bare Copper
4	22	7x30	BC - Bare Copper
4	18	7x26	BC - Bare Copper

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)	AWG
PP - Polypropylene	0.203	22
PP - Polypropylene	0.203	18

Insulation Color Code Chart:

Color	Description
Black	Door Contact 1
Red	Door Contact 2
Black	Rex/Spare 1
Red	Rex/Spare 2
White	Rex/Spare 3
Green	Rex/Spare 4
Black	Lock/Power 1
Red	Lock/Power 2
White	Lock/Power 3
Green	Lock/Power 4

558AFS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Individual Shield

Outer Shield

Outer Shield Material:

AWG	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)	Description
22	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Door Contact
22	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Rex/Spare
18	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Lock/Power

Outer Shield Drain Wire AWG:

Component	AWG	Stranding	Drain Wire Conductor Material
Door Contact	24	(7x32)	TC - Tinned Copper
Rex/Spare	24	(7x32)	TC - Tinned Copper
Lock/Power	24	(7x32)	TC - Tinned Copper

Outer Jacket

Outer Jacket Diameter:

Component #	Nom. Dia. (mm)
Door Contact	3.353
Rex/Spare	3.835
Lock/Power	4.928

Outer Jacket Ripcord: Yes

Outer Jacket Color Code Chart:

Number	Color
Door Contact	White
Rex/Spare	Blue
Lock/Power	Gray

Applicable Specifications and Agency Compliance

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

NEC Articles: 800

CEC/C(UL) Specification: CMG

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Capacitance Conductor to Shield:

Description	Freq. (MHz)	Capacitance (pF/m)
Door Contact	1.000	203.422
Rex/Spare	1.000	131.240
Lock Power	1.000	159.129

Nom. Capacitance Conductor to Conductor:

Description	Freq. (MHz)	Capacitance (pF/m)
Door Contact	1.000	113.195
Rex/Spare	1.000	73.823
Lock Power	1.000	88.587

Nom. Conductor DC Resistance:

Description	DCR @ 20°C (Ohm/km)
Door Contact	53.808
Rex/Spare	53.808
Lock Power	21.327

Nom. Inner Shield DC Resistance:

Description	DCR @ 20°C (Ohm/km)
Door Contact	52.824
Rex/Spare	52.824

METRIC MEASUREMENT VERSION

558AFS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Lock Power	23.623
------------	--------

Max. Operating Voltage - UL:

Description
300 V RMS

Max. Recommended Current:

Description	Current
Door Contact	2.2 Amps @ 25C ambient
Rex/Spare	2.2 Amps @ 25C ambient
Lock Power	4 Amps @ 25C ambient

Physical Characteristics (Overall)

Conductor

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
Unjacketed

Overall Cable

Overall Nominal Diameter: 11.379 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: 0°C To +75°C

Bulk Cable Weight: 144.355 Kg/Km

Max. Recommended Pulling Tension: 889.640 N

Min. Bend Radius/Minor Axis: 111.760 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Applicable Patents:

Country
www.belden.com/p

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 658AFS

Notes (Overall)

Notes: Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
558AFS 0001000	1,000 FT	106.000 LB	NONE	C	3P22+2C22+4C22+4C18 IFS CMR BP

METRIC MEASUREMENT VERSION

558AFS Composite - Lock Power, Card Reader, Door Contact, REX Applications

558AFS 000500	500 FT	53.500 LB	NONE	C	3P22+2C22+4C22+4C18 IFS CMR BP
---------------	--------	-----------	------	---	--------------------------------

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 01-20-2015

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.