



For more Information  
please call

1-800-Belden1



### General Description:

10 AWG stranded (7x18) bare copper conductors, 12 AWG bare copper ground wire, .045x1A; (1.14mm) XLPE insulation, PVC inner jacket, aluminum interlocked armor, PVC outer jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
3	10	7x18	BC - Bare Copper

Total Number of Conductors: 3

#### Ground Wire

Ground Wire (Y/N): Y

Ground Wire AWG: 12

Ground Wire Stranding: 7x20

Ground Wire Conductor Material: BC - Bare Copper

#### Insulation

Insulation Material:

Insulation Material
XLP - Cross Linked Polyolefin

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	1.600

Outer Jacket Diameter:

Nom. Dia. (mm)
14.351

Outer Jacket over Armor (y/n): Y

#### Outer Jacket over Armor

Outer Jacket Material Over Armor:

OJ Over Armor Material	Dia. (mm)
PVC - Polyvinyl Chloride	22.504

#### Armor

Armor Type: Interlocked

Armor Material: Aluminum

Diameter over Armor: .79

#### Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	Black
2	Red
3	Blue

### Mechanical Characteristics (Overall)

Installation Temperature Range: -25°C To +90°C

Wet Temperature Range: -40°C To +90°C

Dry Temperature Range: -40°C To +90°C

Bulk Cable Weight: 578.910 Kg/Km

Max. Recommended Pulling Tension: 889.640 N

Min. Bend Radius/Minor Axis: 271.780 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

CSA Specification:	C22.2 #131 1000V Tech90, C22.2 #174 HL BCD, Clause 4.31 Low Acid Test
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

### Flame Test

CSA Flame Test:	FT4
-----------------	-----

### Suitability

Suitability - Burial:	Yes
Sunlight Resistance:	Yes

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)	3.412
---------------------	-------

### Max. Recommended Current:

Current	40 Amps per conductor @ 30°C
---------	------------------------------

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 3    Revision Date: 04-27-2016

© 2017 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.